



TOP SCRUB PRO™

High-Performance Top Scrub Solution



Top Scrub Pro is formulated for professional floor care experts. The unique formula aids in the removal of the top layers of floor finish, making it easy to remove embedded stains, soils and black marks while keeping undamaged finish on the floor. With Top Scrub Pro, your floor will be clean and ready for recoating. Use Top Scrub Pro for all your scrub and recoat jobs – it's that simple!



WAREHOUSE DIRECT
WORKPLACE SOLUTIONS

Making Your Workplace More Productive

Toll Free: (800) 858-1180 | **Email:** customerservice@warehousedirect.com

Address: 2001 S Mount Prospect Rd Des Plaines, IL 60018 | **Phone:** (847) 631-3470

TOP SCRUB PRO™

FEATURES

- Uniquely formulated for top scrub applications
- Designed to use with low speed or auto scrubber floor care equipment
- Formula can be used with hot or cold water
- Buffered to pH = 10.0 at dilution to enable efficient and controlled removal of top coats of finish

BENEFITS


- Top scrubbing and recoating saves time and labor, ultimately saving you money
- Fast and effective on tough soils and stains
- Simplifill ensures proper dilution for every bottle, bucket, or tank
- Safely and easily dispense product, just ATTACH - DISPENSE - CLEAN

SPECIFICATION DATA

Dilution	1 oz/gal
pH	11.0 – 12.0 (10.0 @ 1 oz/gal)
Color	Green
Fragrance	Pleasant
Specific Gravity @ 24°C/75°F	1.030
Stability: Shelf @ 24°C/75°F	1 year minimum
Stability: Freeze/Thaw	1 cycle minimum

ADDITIONAL RESOURCES

Scan the QR code to access this product's safety information and documentation.



DIRECTIONS FOR USE

Note: Top Scrub Pro may be used on all surfaces not harmed by water: floors, walls, woodwork, marble, plastic, metal.

TO FILL THE BUCKET OR AUTO SCRUBBER TANK

Attach a water source to the Simplifill quick-connect attachment. Turn on water. Press down on the trigger and slide the lock to continuously dispense product.

MOP AND 175 RPM FLOOR MACHINE

Dust mop floor. Fill bucket with Top Scrub Pro. Mop on Top Scrub Pro and allow solution to dwell for 5 – 10 minutes. Scrub the floor using a pad appropriate for the machine weight, floor finish, and soil level. Pick up the dirty solution and rinse the floor with clean water. Repeat this process as necessary until all embedded soils are removed. Damp mop edges and any residue left on floor. Repeat this process as necessary until all residual soils are removed. Make sure to wipe down baseboards. Allow the floor to dry thoroughly before applying finish.


AUTO SCRUBBER DIRECTIONS

Dust mop floor. Fill tank with Top Scrub Pro. Scrub the floor using an auto scrubber and the appropriate red, blue, or surface prep pad. Pick up the dirty solution and rinse the floor with clean water. Repeat this process as necessary until all embedded soils are removed. Damp mop edges and any residue left on floor. Make sure to wipe down baseboards. Allow the floor to dry thoroughly before applying finish.

ORDERING INFORMATION



#208022



SAFETY: For institutional and industrial use only. Be sure to read all directions, precautionary and first aid statements on product labels before using this or any other Spartan product. If questions remain, consult your employer or a physician. Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor and at www.spartanchemical.com. Workplace labels are available in English, Spanish, and French.

GUARANTEE: Spartan's modern manufacturing and laboratory control ensures uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within 12 months of the date of manufacture.



12/24 L2080

WAREHOUSE DIRECT®
WORKPLACE SOLUTIONS

Making Your Workplace More Productive

Toll Free: (800) 858-1180 | Email: customerservice@warehousedirect.com

Address: 2001 S Mount Prospect Rd Des Plaines, IL 60018 | Phone: (847) 631-3470